

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
11 December 2003 (11.12.2003)

PCT

(10) International Publication Number
WO 03/101256 A1

(51) International Patent Classification⁷: **A47C 19/02,**
F16B 12/02

(21) International Application Number: PCT/IT02/00352

(22) International Filing Date: 31 May 2002 (31.05.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicants and

(72) Inventors: **MAZZA, Tommaso** [IT/IT]; Via Armando
Diaz, 8, I-64100 Teramo (IT). **SALERNI, Alfredo** [IT/IT];
Via Cesare Averardi, 5, I-64100 Teramo (IT).

(74) Agents: **IACOBELLI, Daniele** et al.; Società Italiana
Brevetti S.p.A., Piazza di Pietra, 39, I-00186 Rome (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A SYSTEM FOR A MULTIPLACE COTS STRUCTURE



(57) Abstract: A system for implementing a modular structure having two or more cot places, characterised in that the modular structure is implemented by the mutual interconnection of single units (1) made of a pair of posts (2) and of at least one crosspiece (3) assembled in a sandwich arrangement blocked in position by fastening means (4). The system has the main advantage of providing a variable structural modularity to assume a plurality of different conditions, both with regard to the combinability thereof in terms of number of cot places and with regard to the overall dimensions thereof, while maintaining the same number of cot places, according to the varying of the user's needs over time.

WO 03/101256 A1

WO 03/101256

PCT/IT02/00352

"A SYSTEM FOR A MULTIPLACE COTS STRUCTURE"

DESCRIPTION

The present invention refers to a system for implementing a multiplace cots structure of the type having a variable morphology wherein it is provided a plurality of longitudinal beams of a fixed size and apt to be assembled each to the other, needwise, in different arrangements to generate different arrangements of cots.

Multiplace cots structures are already known to the state of the art, typically providing a first load bearing structure to which there are made integral different transverse members supporting a respective cot seat and that generate likewise respective cot places. Typically, these structures provide two, three, and at times four cot places, arranged in a vertical stacked manner.

Such multiplace cots structures, though very practical and easy to manufacture, entail a first drawback of foreseeing no modularity whatsoever with regard to the possibility of arranging the same number of cots in different arrangements, side-by-side as well as stacked.

Moreover, a second drawback lies in that they do not provide, for a fixed number of cot place a variable size according to the needs and spaces available to the user.

Therefore, object of the present invention is to overcome the abovementioned drawbacks providing a multiplace cots structure which foresees a structural modularity in order to allow the same to assume a plurality of different arrangements, with regard both to its combinability in terms of number of cot places and to its overall size for a fixed, number of available cot places.

Another object of the present invention is to provide a multiplace cots structure which foresees the possibility of assuming different combinations according to the varying of the user's needs over time and allowing

-2-

the user to keep the same number of modular units.

Hence, the present invention provides a system for implementing a modular structure with two or more cot places according to Claim 1.

5 The system of the present invention will hereinafter be better illustrated by the detailed description of a preferred embodiment thereof, given by way of a non-limiting example, making reference to the attached drawings, wherein:

10 Fig. 1 is an exploded partial view of a single unit forming the system to make a modular structure with two or more cot places according to the present invention;

Fig. 2 is an exploded partial view of a detail of a modular structure according to the system of the present invention;

15 Fig. 3 is a perspective view of an arrangement of a modular structure having three cot places according to the system of the present invention;

Fig. 4 is a perspective view of a modular structure having four cot places according to the system of the present invention;

20 Fig. 5 is a front elevational view of a modular structure having three cot places in a first condition; and

25 Fig. 6 is a front elevational view of a modular structure having three cot places in a second condition.

With reference now to Fig. 1, the structure of a single unit for implementing the system according to the present invention is illustrated.

30 More precisely, a single unit 1 is made of a pair of posts 2 of a substantially parallelepiped shape, which may be manufactured in a solid or in a boxed material. Moreover, the single unit 1 provides that between the two posts there may be mounted in a locked manner a plurality
35 of girders 3 (or more simply, crosspieces 3), that are blocked in position by virtue of blocking means as bolts 4 or the like, and apt to be inserted in a respective

-3-

plurality of blocking regions 5 obtained on each post 2 as well as on each crosspiece 3.

Thus, it is provided that a pair of posts 2 may block therebetween a respective plurality of crosspieces 3, thereby implementing a sandwich structure.

On the other hand, the present invention provides a further plurality of head members 6 of a substantially plane and rectangular shape, apt to be blocked between two single units 1 so as to implement the distance for the cot seat between two posts 1.

With particular reference now to Fig. 2, for the blocking of each head member 6 onto the single units 1 it is provided a respective blocking member 7, shaped as a rectangular drilled flathead pin apt to be mounted between the two posts 2 of the unit 1 and to be blocked therein by a respective pin 4 in a respective blocking region 5. Subsequently to the fitting of the pin 7 into the unit 1, the former is made integral to the head member 6 by screws or pins 8 or the like.

Moreover, the invention further provides a respective plurality of substantially C-shaped supporting members 9 for supporting a corner region of a respective bed structure 10 in the already known manner.

Each supporting member 9 is apt to be removably mounted on a respective post 2, and to be blocked in a blocking region 5 with a suitable pin 4.

With reference now to Figs. 3 to 6, different embodiments of multiplace cots structures according to the system of the present invention are illustrated.

As it is apparent from the figures, according to the system of the present invention modular structures can advantageously be implemented in which there can be arranged cots in a side-by-side or stacked condition, varying the extension or the size thereof in the direction of the length of the structure, without however modifying the overall size of the cot places.

More precisely, as it is apparent from Figs. 5 and

- 4 -

6, according to the user's needs it is possible to vary both the height from the floor of each cot, by changing the fastening position of the supporting members 9 in the blocking regions 5, and the overall dimensions of the
5 multiplace cots structure in the longitudinal direction, changing the blocking position of the girders 3 onto the posts 2.

The present invention entails several advantages. A first advantage lies in that the system meets the needs
10 of all users, according to the space available thereto, for any arrangement and number of cot places.

A second advantage lies in that the same number of cot places can be maintained, changing however the overall dimensions of the modular structure assembled
15 according to the system of the present invention.

A further advantage lies in that the present invention is not limited to the abovedescribed embodiments. E.g., single units 1 can have any shape or can be made of any suitable material still maintaining
20 this function.

CLAIMS

1. A system for implementing a modular structure having two or more cot places comprising a first plurality of posts (2), a second plurality of crosspieces (3), and a plurality of head members (6),

characterised in that said modular structure is implemented by mutual interconnection of single units (1) comprising a pair of posts (2) and at least one crosspiece (3) assembled in a sandwich arrangement blocked in position by fastening means (4).

2. The system for implementing a modular structure having two or more cot places according to claim 1, wherein each post (2) of said plurality of posts (2) has a plurality of blocking regions (5) apt to cooperate with said fastening means for the mutual interconnection of said single units (1).

3. The system for implementing a modular structure having two or more cot places according to claim 1 or 2, wherein each crosspiece (3) of said plurality of crosspieces (3) has a plurality of blocking regions (5) apt to cooperate with said fastening means for the mutual interconnection of said single units (1).

4. The system for implementing a modular structure having two or more cot places according to claim 1 or 2 or 3, wherein each post (2) of said plurality of posts (2) is substantially rectangular-section beam shaped.

5. The system for implementing a modular structure having two or more cot places according to any one of the preceding claims, wherein each crosspiece (3) of said plurality of crosspieces (3) is substantially rectangular-section beam shaped.

6. The system for implementing a modular structure having two or more cot places according to claim 4 or 5, wherein each post (2) of said plurality of posts (2) and each crosspiece (3) of said plurality of crosspieces (3) is substantially made of a boxed rectangular-section

- 6 -

beam.

7. The system for implementing a modular structure having two or more cot places according to any one of the preceding claims, wherein each head member of said
5 plurality of head members is a substantially rectangular-shaped plane member (6) apt to be blocked between two single units (1) by second blocking means (7,8).

8. The system for implementing a modular structure having two or more cot places according to the preceding
10 claim, wherein said second blocking means comprises an anchoring member (7) apt to be assembled between two posts (2) of a single unit (1) in a sandwich arrangement.

9. The system for implementing a modular structure having two or more cot places according to any one of the
15 preceding claims, further comprising supporting means (9) of a respective cot seat and removably assembled on said single unit (1).

"A SYSTEM FOR A MULTIPLACE COTS STRUCTURE"

ABSTRACT

5 A system for implementing a modular structure having
two or more cot places, characterised in that the modular
structure is implemented by the mutual interconnection of
single units (1) made of a pair of posts (2) and of at
least one crosspiece (3) assembled in a sandwich
arrangement blocked in position by fastening means (4).
The system has the main advantage of providing a variable
10 structural modularity to assume a plurality of different
conditions, both with regard to the combinability thereof
in terms of number of cot places and with regard to the
overall dimensions thereof, while maintaining the same
number of cot places, according to the varying of the
15 user's needs over time.




FIG. 2




FIG. 1




FIG.3




FIG.4




FIG. 5




FIG. 6

INTERNATIONAL SEARCH REPORT

PCT/IT 02/00352

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A47C19/02 F16B12/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A47C F16B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 514 841 A (MOUGEL HENRI) 22 April 1983 (1983-04-22) page 2; figures 1,2,5,7 -----	1,4-7
A	US 5 572 751 A (BRANDT JAMES C) 12 November 1996 (1996-11-12) -----	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

22 January 2003

Date of mailing of the international search report

03/02/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Novelli, B

INTERNATIONAL SEARCH REPORT

PCT/IT 02/00352

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
FR 2514841	A	22-04-1983	FR	2514841 A1	22-04-1983
US 5572751	A	12-11-1996	NONE		